## NSN 5306-01-253-7118

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-253-7118



## Thread Class:

3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.742 inches and 0.792 inches

## Fastener Length:

Between 2.002 inches and 2.032 inches

### Head Style:

Double hexagon w/hole

## **Head Height:**

Between 0.494 inches and 0.514 inches

## Width Between Flats:

0.564 inches

### **Extended Washer Diameter:**

Between 0.818 inches and 0.828 inches

### **Extended Washer Thickness:**

Between 0.113 inches and 0.133 inches

## **Grip Diameter:**

Between 0.4990 inches and 0.4995 inches

## Thread Diameter:

0.500 inches

Grip Length:

Between 1.240 inches and 1.260 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

220000 pounds per square inch

## Material:

Steel comp xm-13

## **Material Specification:**

Ams5629 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-01-253-7118

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

