## NSN 5306-01-253-9022

Close Tolerance Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-253-9022



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.366 inches and 0.416 inches Fastener Length: Between 1.501 inches and 1.531 inches **Head Style:** Hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches Shank Unthreaded Hole Diameter: 0.106 inches first hole and 0.116 inches first hole **Thread Diameter:** 0.375 inches Grip Length: Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.373 inches first hole and 1.423 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas656 professional/industrial association standard Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

## NSN 5306-01-253-9022

Close Tolerance Bolt - Page 2 of 2

Fiig: A003b0

