NSN 5306-01-254-0849

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-254-0849

view Offilite at https://aerobasegroup.com/hist//3500-01-254-0
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.568 inches and 0.618 inches
Fastener Length:
Between 0.890 inches and 0.920 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.266 inches and 0.286 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.072 inches and 0.092 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-01-254-0849

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0