

View Online at <https://aerobasegroup.com/nsn/5306-01-254-0854>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.699 inches and 0.766 inches

Fastener Length:

Between 2.084 inches and 2.131 inches

Head Style:

Double hexagon

Head Height:

Between 0.318 inches and 0.338 inches

Width Between Flats:

0.877 inches

Grip Diameter:

Between 0.5610 inches and 0.5615 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Thread Diameter:

0.562 inches

Grip Length:

Between 1.365 inches and 1.385 inches

Thread Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.955 inches first hole and 2.012 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0