NSN 5306-01-254-3745

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-254-3745 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 2.454 inches and 2.484 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Hole Diameter:** Between 0.070 inches and 0.080 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.3125 inches **Grip Length:** Between 1.980 inches and 2.010 inches Thready Qty Per Inch (tpi): 24 **Hole Configuration Style:**

Hexagon corners

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416a, type ii, cls 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas6605 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5306-01-254-3745

Shear Bolt - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.