NSN 5306-01-254-3746

Shear Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-01-254-3746 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.469 inches |
| Fastener Length: |
| Between 2.329 inches and 2.359 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.156 inches and 0.171 inches |
| Width Between Flats: |
| Between 0.492 inches and 0.502 inches |
| Hole Diameter: |
| Between 0.070 inches and 0.080 inches |
| Grip Diameter: |
| Between 0.3110 inches and 0.3120 inches |
| Thread Diameter: |
| 0.3125 inches |
| Grip Length: |
| Between 1.865 inches and 1.885 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Hole Configuration Style: |
| Hexagon corners |
| Material: |
| Steel comp e4340 or steel comp 8740 |
| Material Specification: |
| Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard |
| 2nd material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416a, typ ii, cls 2 federal specification all treatment responses |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas6605 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5306-01-254-3746

Shear Bolt - Page 2 of 2



| _ | | | | | | |
|----|-----|---------|-----|-----|----|--|
| 11 | em) | tor | 172 | + 1 | nn | |
| | | | | | | |

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.