## NSN 5306-01-255-4610

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-255-4610 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.130 inches **Fastener Length:** Between 0.688 inches and 0.692 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** Between 0.125 inches and 0.130 inches **Second Diameter From Head:** Between 0.095 inches and 0.100 inches Third Diameter From Head: Between 0.158 inches and 0.164 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.243 inches and 0.252 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.453 inches and 0.467 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 0.518 inches and 0.522 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.1406 inches and 0.1426 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity: Product Name:** 

Navy special project

Material:

Iron alloy 660

**Material Specification:** 

Ams5731 assn standard single material response or ams5737 assn standard single material response

## NSN 5306-01-255-4610

Internal Wrenching Bolt - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0