## NSN 5306-01-256-4454

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-256-4454

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.579 inches and 0.619 inches **Fastener Length:** Between 1.089 inches and 1.109 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.338 inches and 0.358 inches Width Between Flats: Between 0.365 inches and 0.385 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** Between 0.072 inches and 0.092 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip **Product Name:** Navy special project **Special Features:** Finish color olive drab green Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Ceramic

## **Surface Treatment Specification:**

Mil-c-81751, type 1 class 4 military specification single treatment response

## NSN 5306-01-256-4454

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-c-81751 spec.