

View Online at <https://aerobasegroup.com/nsn/5306-01-256-5167>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.615 inches and 0.775 inches

Shank Length:

Between 0.715 inches and 0.775 inches

Eye Stock Diameter:

0.688 inches

Shoulder Diameter:

Between 0.554 inches and 0.559 inches

Shoulder Length:

Between 3.990 inches and 4.010 inches

Ring Stock Diameter:

Between 0.355 inches and 0.395 inches

Thread Diameter:

0.438 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Product Name:

Navy special project

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification 1st treatment response or qq-z-325 ty2 cl3 federal specification 2nd treatment response

Style Designator:

Swivel

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0