Internally Relieved Body Bolt - Page 1 of 2





Thre	ad Class:
2a	
Thre	ad Direction:
Righ	t-hand
	ead Length:
	veen 0.578 inches and 0.640 inches
Fast	ener Length:
0.64	0 inches
Hea	d Style:
Flat	countersunk undercut
Hea	d Diameter:
0.35	0 inches
Hea	d Height:
	0 inches
Hole	Diameter:
0.09	3 inches
Thre	ead Diameter:
0.19	0 inches
Hole	Quantity:
1	
Hole	э Туре:
Drille	ed
Thre	eady Qty Per Inch (tpi):
32	
Hole	Configuration Style:
Rou	nd longitudinal hole
Cou	ntersink Angle:
82.0	degrees
Spe	cial Features:
Cou	ntersunk hole 0.170 in. Diameter on head; 0.310 in. Width across flats
Mate	erial:
Stee	l comp 303
Mate	erial Specification:
Astn	n a582 assn standard single material response
Surf	ace Treatment:
Pass	sivate
Surf	ace Treatment Specification:
Qq-p	p-35 federal specification single treatment response
Styl	e Designator:
Con	centric hole threaded
Thre	ad Series Designator:
Unf	

## NSN 5306-01-256-5183

Internally Relieved Body Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

