

View Online at <https://aerobasegroup.com/nsn/5306-01-256-6828>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.165 inches and 0.205 inches

Fastener Length:

Between 1.810 inches and 1.840 inches

Head Style:

Undercut hexagon

Head Height:

0.188 inches

Width Between Flats:

0.750 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

First Diameter From Head:

0.438 inches

Second Diameter From Head:

Between 0.397 inches and 0.399 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.935 inches and 0.945 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.438 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.635 inches first hole and 1.645 inches first hole

Externally Relieved Body Diameter Quantity:

2

Special Features:

Organic finish on shank, s2 type 1 per bps 4310

Material:

Steel comp 4140 or steel comp 4340

Material Specification:

Mil-s-5626 cond c4 military specification 1st material response or mil-s-5000 cond c4 military specification 2nd material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.