
## NSN 5306-01-256-6834

Shear Bolt - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.552 inches and 0.604 inches

#### Fastener Length:

Between 2.250 inches and 2.282 inches

## Head Style:

Hexagon

Head Height:

Between 0.211 inches and 0.235 inches

#### Width Between Flats:

Between 0.554 inches and 0.564 inches

#### Hole Diameter:

Between 0.070 inches and 0.080 inches

#### Grip Diameter:

Between 0.3737 inches and 0.3742 inches

#### **Thread Diameter:**

0.375 inches

Grip Length:

Between 1.678 inches and 1.698 inches

## Hole Quantity:

1

#### Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

## Hole Configuration Style:

Hexagon flats

#### Material:

Iron alloy 660

## **Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

# NSN 5306-01-256-6834

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

