

View Online at <https://aerobasegroup.com/nsn/5306-01-256-6838>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.848 inches and 0.898 inches

Fastener Length:

Between 4.608 inches and 4.638 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.608 inches and 0.628 inches

Width Between Flats:

Between 0.682 inches and 0.691 inches

Extended Washer Diameter:

Between 1.040 inches and 1.050 inches

Extended Washer Thickness:

Between 0.140 inches and 0.160 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 3.740 inches and 3.760 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas630 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0