

View Online at <https://aerobasegroup.com/nsn/5306-01-258-6021>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.310 inches and 0.360 inches

Fastener Length:

Between 1.018 inches and 1.048 inches

Head Style:

Hexagon

Head Height:

Between 0.140 inches and 0.172 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Shoulder Diameter:

0.2490 inches all shoulders and 0.2495 inches all shoulders

Shoulder Length:

0.688 inches all shoulders and 0.708 inches all shoulders

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.845 inches first hole and 0.895 inches first hole

Shoulder Shape:

Round all shoulders

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0