# NSN 5306-01-258-9094

Machine Bolt - Page 1 of 2





# Thread Class:

3a

**Thread Direction:** 

Right-hand

### Thread Length:

Between 0.812 inches and 0.872 inches

#### Fastener Length:

Between 1.202 inches and 1.232 inches

#### Head Style:

Hexagon

Head Height:

Between 0.265 inches and 0.297 inches

#### Width Between Flats:

Between 0.741 inches and 0.751 inches

#### **Thread Diameter:**

0.500 inches

# Grip Length:

Between 0.360 inches and 0.390 inches

#### Features Provided:

Finished head

### Thready Qty Per Inch (tpi):

20

#### Min. Tensile Strength (psi):

140000 pounds per square inch

#### Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

#### **Minimum Yield Strength:**

85000 pounds per square inch

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5732 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas1008 professional/industrial association standard

## Shelf Life:

N/a

# NSN 5306-01-258-9094

Machine Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

