NSN 5306-01-258-9103

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-258-9103

View Offline at https://derobasegroup.com/nsn/3300-01-230-3103
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.429 inches and 0.479 inches
Fastener Length:
Between 1.877 inches and 1.907 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.428 inches and 1.448 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon flats
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification single material response or ams6322 assn standard single material response
Surface Treatment:
Chromate
Surface Treatment Specification:

Qq-p-416 type 2, class 2 federal specification single treatment response

NSN 5306-01-258-9103

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Fiig: A003b0

Mil-std (military Standard):

Mil-s-5000 spec.