Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-259-6001

New Online at https://defobasegroup.com/nsi//3500-01-253-0001	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.942 inches	
Fastener Length:	
1.970 inches	
Head Style:	
Hexagon	
Head Height:	
0.310 inches	
Width Between Flats:	
0.500 inches	
Point Length:	
0.030 inches	
First Diameter From Head:	
Between 0.310 inches and 0.316 inches	
Second Diameter From Head:	
Between 0.180 inches and 0.200 inches	
Third Diameter From Head:	
0.189 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
0.475 inches	
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:	
0.950 inches	
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:	
1.028 inches	
Point Style:	
Flat	
End Application:	
Peacekeeper t and h, horizontal adjusting	
Thread Diameter:	
0.250 inches	
Thready Qty Per Inch (tpi):	
28	
Externally Relieved Body Diameter Quantity:	
3	
Point Chamfer Angle:	
45.0 degrees	
Material:	
Stainless steel	

NSN 5306-01-259-6001

Externally Relieved Body Bolt - Page 2 of 2



Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 type i federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0