

View Online at <https://aerobasegroup.com/nsn/5306-01-260-0424>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.945 inches and 0.995 inches

Fastener Length:

Between 4.205 inches and 4.235 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.484 inches and 0.504 inches

Width Between Flats:

Between 0.679 inches and 0.690 inches

Extended Washer Diameter:

Between 1.040 inches and 1.050 inches

Extended Washer Thickness:

Between 0.140 inches and 0.160 inches

Grip Diameter:

Between 0.6235 inches and 0.6240 inches

Thread Diameter:

0.625 inches

Grip Length:

Between 3.240 inches and 3.260 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0