

View Online at <https://aerobasegroup.com/nsn/5306-01-261-1873>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

Between 0.972 inches and 1.002 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.429 inches and 0.439 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:**

0.2500 inches

**Grip Length:**

Between 0.552 inches and 0.572 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Material:**

Steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response and mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification 1st treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6604 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.