

View Online at <https://aerobasegroup.com/nsn/5306-01-262-3491>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.458 inches and 0.478 inches

Fastener Length:

Between 0.891 inches and 0.921 inches

Head Style:

Spline extended washer

Head Height:

Between 0.240 inches and 0.260 inches

Extended Washer Diameter:

Between 0.460 inches and 0.470 inches

Extended Washer Thickness:

Between 0.026 inches and 0.046 inches

Grip Diameter:

Between 0.249 inches and 0.250 inches

Head Minor Diameter:

Between 0.235 inches and 0.250 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.428 inches and 0.448 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

220000 pounds per square inch

Material:

Steel comp xm-13

Material Specification:

Ams 5629, uns s13800 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Supplementary Features:

Wrenching element ms33787-10, hd mk nas1347 type 4

Thread Series Designator:

Unjf

Specification Data:

76301-st3-753 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0