## NSN 5306-01-262-5410

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-262-5410 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** Between 0.928 inches and 0.948 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** Between 0.055 inches and 0.075 inches **First Diameter From Head:** Between 0.222 inches and 0.232 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.128 inches and 0.188 inches **Thread Diameter:** 0.250 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Double hexagon flats **Externally Relieved Body Diameter Quantity:** Material: Nickel alloy 718 **Material Specification:** Cs0tf13cl-b assn standard single material response **Thread Series Designator:** 

Unjf

## NSN 5306-01-262-5410

Externally Relieved Body Bolt - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0