NSN 5306-01-262-9012



Close Tolerance Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-262-9012 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.443 inches and 0.493 inches **Fastener Length:** Between 1.078 inches and 1.108 inches **Head Style:** Spline extended washer **Head Height:** Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.460 inches and 0.470 inches **Extended Washer Thickness:** Between 0.026 inches and 0.046 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Head Minor Diameter:** Between 0.297 inches and 0.312 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 28 **Special Features:** Thread hole in top of head 0.138-32 unjc-3b thds; injection port 0.120 in. Lg, 0.060 in. Wide in unthd shank; distant from head to beginning of injection port 0.350 in. Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unit Of Measure:

Shelf Life:

Unjf

N/a

NSN 5306-01-262-9012

Close Tolerance Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0