

View Online at <https://aerobasegroup.com/nsn/5306-01-263-8103>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.698 inches and 0.738 inches

**Fastener Length:**

Between 1.635 inches and 1.665 inches

**Head Diameter:**

Between 0.740 inches and 0.750 inches

**Head Height:**

Between 0.428 inches and 0.448 inches

**Hole Diameter:**

Between 0.055 inches and 0.060 inches

**Internal Drive Style:**

Hexagon

**End Application:**

Spec item

**Thread Diameter:**

0.438 inches

**Width Across Flats:**

Between 0.313 inches and 0.315 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

34.0 rockwell c and 40.0 rockwell c

**Hole Configuration Style:**

Round internal hexagon

**Surface Finish:**

63.0 microinches bearing surface of head

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0