View Online at https://aerobasegroup.com/nsn/5306-01-263-8119

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.788 inches and 0.838 inches

Fastener Length:

Between 3.110 inches and 3.140 inches

Head Style:

Bevel-conical

Head Diameter:

Between 0.802 inches and 0.813 inches

Head Height:

Between 0.396 inches and 0.416 inches

Hole Diameter:

Between 0.070 inches and 0.075 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.500 inches

Width Across Flats:

Between 0.500 inches and 0.503 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.927 inches first hole and 2.947 inches first hole

Material:

Steel comp e4340 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas148 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0