

View Online at <https://aerobasegroup.com/nsn/5306-01-263-8496>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.504 inches and 0.540 inches

Fastener Length:

Between 1.958 inches and 1.978 inches

Head Style:

Hexagon

Head Height:

Between 0.156 inches and 0.172 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Locking Feature:

Detent ball grip

Grip Diameter:

Between 0.3112 inches and 0.3117 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

Between 1.438 inches and 1.454 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.872 inches first hole and 1.902 inches first hole

Surface Finish:

63.0 microinches grip

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0