

View Online at <https://aerobasegroup.com/nsn/5306-01-264-1450>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 4.730 inches and 4.930 inches

Fastener Length:

6.060 inches

Head Style:

Hexagon extended washer

Head Height:

0.840 inches

Width Between Flats:

Between 0.865 inches and 0.875 inches

Extended Washer Diameter:

1.380 inches

Extended Washer Thickness:

0.125 inches

Shoulder Diameter:

0.812 inches first shoulder

Shoulder Length:

1.130 inches first shoulder

Shank Unthreaded Hole Diameter:

0.250 inches first hole and 0.255 inches first hole

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

10

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.910 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ps13001, cagc 76301 mfr ref single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0