## NSN 5306-01-264-3588

Shoulder Bolt - Page 1 of 2

3a

20

Unjf



**Thread Class: Thread Direction: Right-hand Thread Length:** 0.733 inches Fastener Length: Between 2.218 inches and 2.248 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** Between 0.089 inches and 0.109 inches Shoulder Diameter: 0.4516 inches first shoulder and 0.4526 inches first shoulder Shoulder Length: 1.490 inches first shoulder and 1.510 inches first shoulder **Thread Diameter:** 0.4375 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch Shoulder Shape: Round first shoulder Color: Black threads Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Bms10-85 type 1, cage 81205 mfr ref single treatment response **Thread Series Designator:** 

## NSN 5306-01-264-3588

Shoulder Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

