## NSN 5306-01-264-9143

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-264-9143 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.298 inches and 0.420 inches **Fastener Length:** Between 0.813 inches and 0.905 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.186 inches and 0.206 inches Width Between Flats: 0.251 inches **Extended Washer Diameter:** Between 0.340 inches and 0.350 inches **Extended Washer Thickness:** Between 0.054 inches and 0.074 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.485 inches and 0.515 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Surface Finish: 32.0 microinches grip Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-01-264-9143

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0