

View Online at <https://aerobasegroup.com/nsn/5306-01-265-2058>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.602 inches and 0.662 inches

**Shank Length:**

Between 0.602 inches and 0.662 inches

**Eye Stock Diameter:**

0.562 inches

**Shoulder Diameter:**

Between 0.368 inches and 0.373 inches

**Shoulder Length:**

Between 1.490 inches and 1.510 inches

**Shank Unthreaded Hole Diameter:**

0.066 inches first hole and 0.086 inches first hole

**Ring Stock Diameter:**

Between 0.230 inches and 0.270 inches

**Ring Inside Diameter:**

Between 0.178 inches and 0.198 inches

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Product Name:**

Navy special project

**Special Features:**

Moveable ring

**Material:**

Steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-8503 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate or zinc

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification 1st treatment response or astm b633 assn standard 2nd treatment response

**Style Designator:**

Swivel

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1251 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.