

View Online at <https://aerobasegroup.com/nsn/5306-01-265-2068>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.580 inches

**Fastener Length:**

2.140 inches

**Head Style:**

Hexagon

**Head Height:**

0.260 inches

**Width Between Flats:**

Between 0.865 inches and 0.875 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Concentric Hole Depth:**

1.790 inches

**Concentric Hole Diameter:**

0.250 inches

**Thread Diameter:**

0.562 inches

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

42.0 rockwell c and 46.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.985 inches first hole and 1.995 inches first hole

**Special Features:**

Cut key way in threaded area

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Chromium

**Surface Treatment Specification:**

La0109-019, cagec 43999 mfr ref single treatment response

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0