

View Online at <https://aerobasegroup.com/nsn/5306-01-265-3356>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.490 inches and 0.557 inches

Fastener Length:

Between 2.625 inches and 2.672 inches

Head Style:

Double hexagon

Head Height:

Between 0.200 inches and 0.220 inches

Width Between Flats:

0.564 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 2.115 inches and 2.135 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.500 inches first hole and 2.557 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0