

View Online at <https://aerobasegroup.com/nsn/5306-01-265-4801>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.888 inches and 0.955 inches

**Fastener Length:**

Between 3.086 inches and 3.133 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.390 inches and 0.410 inches

**Width Between Flats:**

1.064 inches

**Grip Diameter:**

Between 0.7485 inches and 0.7490 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.146 inches first hole

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 2.178 inches and 2.198 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.948 inches first hole and 3.005 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0