NSN 5306-01-265-6120

Shear Bolt - Page 1 of 2



Vie	w Online at https://aerobasegroup.com/nsn/5306-01-265-6120
Thi	read Class:
3a	
Thi	read Direction:
Rig	ht-hand
Thi	read Length:
Bet	ween 1.150 inches and 1.200 inches
Fas	stener Length:
Bet	ween 10.472 inches and 10.502 inches
He	ad Style:
Do	uble hexagon w/hole
He	ad Height:
Bet	ween 0.798 inches and 0.818 inches
Wie	dth Between Flats:
Bet	ween 0.928 inches and 0.940 inches
Ext	tended Washer Diameter:
Bet	ween 1.428 inches and 1.438 inches
Ext	tended Washer Thickness:
Bet	ween 0.188 inches and 0.208 inches
Gri	p Diameter:
Bet	ween 0.873 inches and 0.874 inches
Thi	read Diameter:
0.8	75 inches
Gri	p Length:
Bet	ween 9.302 inches and 9.322 inches
Thi	ready Qty Per Inch (tpi):
14	
Mir	n. Tensile Strength (psi):
220	0000 pounds per square inch
Ha	rdness Rating:
46.	0 rockwell c and 50.0 rockwell c
Su	rface Finish:
32.	0 microinches grip
Pro	oduct Name:
Na	vy special project
Ma	terial:
Ste	el comp h11
Ma	terial Specification:
Am	s 6487 assn standard single material response
_	for a Taxaturant.

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response

NSN 5306-01-265-6120

Shear Bolt - Page 2 of 2



Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A003b0