# NSN 5306-01-266-3051

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-266-3051



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.444 inches and 0.494 inches

#### Fastener Length:

Between 1.266 inches and 1.296 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.156 inches and 0.171 inches

## Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.3110 inches and 0.3120 inches

#### **Thread Diameter:**

0.312 inches

# Grip Length:

Between 0.802 inches and 0.822 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Surface Finish:

32.0 microinches threads

## Material:

Iron alloy 660

## **Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas6705 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5306-01-266-3051

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

