NSN 5306-01-267-0044

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-267-0044

Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.400 inches and 0.455 inches Fastener Length: Between 1.035 inches and 1.065 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches **Grip Diameter:** Between 0.248 inches and 0.249 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.610 inches and 0.635 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6704 professional/industrial association standard Shelf Life: N/a

NSN 5306-01-267-0044

Shear Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

