
NSN 5306-01-268-0904

Machine Bolt - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.740 inches and 0.820 inches Fastener Length: Between 1.115 inches and 1.135 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.315 inches and 0.375 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 175000 pounds per square inch Hardness Rating: 34.0 rockwell c and 44.0 rockwell c Minimum Yield Strength: 115000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Nickel alloy uns n07001 **Material Specification:** Ams 5708 assn standard single material response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-268-0904

Machine Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

