NSN 5306-01-268-0908

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-268-0908

View Online at https://aerobasegroup.com/nsn/5306-01-268-0908
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.345 inches and 0.395 inches
Fastener Length:
Between 0.793 inches and 0.823 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Grip Diameter:
Between 0.2485 inches and 0.2490 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf

NSN 5306-01-268-0908

Shear Bolt - Page 2 of 2



Specification D	ata:
-----------------	------

80205-nas6304 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0