## NSN 5306-01-268-1197

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-268-1197

View Online at https://aerobasegroup.com/nsn/5306-01-268-1197
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.568 inches and 0.618 inches
Fastener Length:
Between 1.516 inches and 1.546 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.290 inches and 0.319 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.040 inches and 0.060 inches
Grip Diameter:
Between 0.3104 inches and 0.3110 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
200000 pounds per square inch
Surface Finish:
32.0 microinches threads
Color:
Green threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5306-01-268-1197

Shear Bolt - Page 2 of 2



		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0