

View Online at <https://aerobasegroup.com/nsn/5306-01-268-5437>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.552 inches and 0.604 inches

Fastener Length:

Between 1.562 inches and 1.594 inches

Head Style:

Hexagon

Head Height:

Between 0.211 inches and 0.235 inches

Width Between Flats:

Between 0.554 inches and 0.564 inches

Grip Diameter:

Between 0.3737 inches and 0.3742 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.375 inches

Grip Length:

Between 0.990 inches and 1.010 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.432 inches first hole and 1.484 inches first hole

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0