

View Online at <https://aerobasegroup.com/nsn/5306-01-268-8809>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.451 inches and 0.511 inches

Fastener Length:

Between 1.091 inches and 1.121 inches

Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.640 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Washer Quantity:

1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

140000 pounds per square inch

Primary Washer Outside Diameter:

0.420 inches

Primary Washer Style:

Finishing

Primary Washer Material Thickness:

Between 0.020 inches and 0.030 inches

Special Features:

Also contains tab, corrosion resistant steel comp 301 per mil-s-5059, passivated

Material:

Steel comp 303se stand-off

Material Specification:

Mil-s-5059 military specification single material response stand-off

Surface Treatment:

Passivate stand-off

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stand-off

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.