NSN 5306-01-268-8809

Assembled Washer Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-268-8809 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.451 inches and 0.511 inches **Fastener Length:** Between 1.091 inches and 1.121 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.640 inches Width Between Flats: Between 0.367 inches and 0.376 inches Washer Quantity: **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch **Primary Washer Outside Diameter:** 0.420 inches **Primary Washer Style:** Finishing **Primary Washer Material Thickness:** Between 0.020 inches and 0.030 inches **Special Features:** Also contains tab, corrosion resistant steel comp 301 per mil-s-5059, passivated Material: Steel comp 303se stand-off **Material Specification:** Mil-s-5059 military specification single material response stand-off **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response stand-off **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-268-8809

Assembled Washer Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.