# NSN 5306-01-268-8809

Assembled Washer Bolt - Page 1 of 2





### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.451 inches and 0.511 inches

#### Fastener Length:

Between 1.091 inches and 1.121 inches

#### Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.640 inches

#### Width Between Flats:

Between 0.367 inches and 0.376 inches

#### Washer Quantity:

## Thread Diameter:

. .

0.190 inches

### Thready Qty Per Inch (tpi):

32

1

#### Min. Tensile Strength (psi):

140000 pounds per square inch

#### Primary Washer Outside Diameter:

0.420 inches

#### **Primary Washer Style:**

Finishing

#### **Primary Washer Material Thickness:**

Between 0.020 inches and 0.030 inches

#### **Special Features:**

Also contains tab, corrosion resistant steel comp 301 per mil-s-5059, passivated

#### Material:

Steel comp 303se stand-off

#### **Material Specification:**

Mil-s-5059 military specification single material response stand-off

#### Surface Treatment:

Passivate stand-off

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stand-off

#### Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5306-01-268-8809

Assembled Washer Bolt - Page 2 of 2

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.