## NSN 5306-01-268-9481



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-268-9481 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** 1.000 inches **Head Style:** Hexagon **Head Height:** Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.5510 inches and 0.5625 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.3690 inches and 0.3750 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 348 or steel comp 348 or steel comp 364 or steel comp 364 or steel comp 365 or steel comp 365 or steel comp 366 or steel comp comp 385 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

## **NSN 5306-01-268-9481**Machine Bolt - Page 2 of 2



Fiig:

A003b0