# NSN 5306-01-269-1488

Shear Bolt - Page 1 of 2





**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

Between 0.399 inches and 0.449 inches

#### Fastener Length:

Between 1.471 inches and 1.501 inches

#### Head Style:

Spline extended washer

### **Head Height:**

Between 0.158 inches and 0.198 inches

# **Extended Washer Diameter:**

Between 0.349 inches and 0.359 inches

### **Extended Washer Thickness:**

Between 0.017 inches and 0.037 inches

### **Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

### Head Minor Diameter:

Between 0.173 inches and 0.188 inches

# Thread Diameter:

0.190 inches

Grip Length:

Between 1.052 inches and 1.072 inches

# Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

# Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

#### Surface Finish:

32.0 microinches grip

Material:

Steel comp h11

# **Material Specification:**

Ams6487 assn standard single material response

# Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Mil-c-8837 ty2 cl2 federal standard single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5306-01-269-1488

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

# Mil-std (military Standard):

Mil-c-8837 spec.

