NSN 5306-01-269-2599

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-01-269-2599

Thread Length:
0.375 inches
Fastener Length:
Between 0.500 inches and 0.530 inches
Head Style:
Double hexagon extended washer
Head Height:
0.196 inches
Width Between Flats:
Between 0.277 inches and 0.290 inches
Extended Washer Diameter:
Between 0.340 inches and 0.350 inches
Extended Washer Thickness:
0.064 inches
Hole Diameter:
Between 0.034 inches and 0.042 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
0.125 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon flats
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response

Surface Treatment:

Passivate

NSN 5306-01-269-2599

Shear Bolt - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0