NSN 5306-01-269-5127

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-269-5127

80205-nas6704 professional/industrial association standard

| Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.395 inches and 0.440 inches Fastener Length: |
|---|
| Thread Direction: Right-hand Thread Length: Between 0.395 inches and 0.440 inches Fastener Length: |
| Right-hand Thread Length: Between 0.395 inches and 0.440 inches Fastener Length: |
| Thread Length: Between 0.395 inches and 0.440 inches Fastener Length: |
| Between 0.395 inches and 0.440 inches Fastener Length: |
| Fastener Length: |
| |
| |
| Between 0.535 inches and 0.565 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.125 inches and 0.140 inches |
| Width Between Flats: |
| Between 0.429 inches and 0.439 inches |
| Locking Feature: |
| Pellet threads or strip threads or patch threads |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.115 inches and 0.135 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Weapon system essential |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |

NSN 5306-01-269-5127

Machine Bolt - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0