## NSN 5306-01-269-5127

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-269-5127

80205-nas6704 professional/industrial association standard

Thread Class:  3a  Thread Direction: Right-hand  Thread Length: Between 0.395 inches and 0.440 inches  Fastener Length:
Thread Direction: Right-hand Thread Length: Between 0.395 inches and 0.440 inches Fastener Length:
Right-hand  Thread Length:  Between 0.395 inches and 0.440 inches  Fastener Length:
Thread Length:  Between 0.395 inches and 0.440 inches  Fastener Length:
Between 0.395 inches and 0.440 inches  Fastener Length:
Fastener Length:
Between 0.535 inches and 0.565 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Locking Feature:
Pellet threads or strip threads or patch threads
Thread Diameter:
0.250 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

## NSN 5306-01-269-5127

Machine Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0