

View Online at <https://aerobasegroup.com/nsn/5306-01-269-7820>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.768 inches

Fastener Length:

Between 1.010 inches and 1.030 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.494 inches and 0.514 inches

Width Between Flats:

Between 0.547 inches and 0.562 inches

Extended Washer Diameter:

Between 0.818 inches and 0.828 inches

Extended Washer Thickness:

0.123 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Hole Configuration Style:

Double hexagon flats

Material:

Steel comp 4140 or steel comp 4340 or steel comp 6150

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 11, cl 2 military standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

96906-ms21250h08006 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0