NSN 5306-01-269-9235

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-269-9235
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.479 inches and 1.519 inches
Fastener Length:
Between 3.114 inches and 3.134 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.913 inches and 0.933 inches
Width Between Flats:
Between 1.047 inches and 1.062 inches
Extended Washer Diameter:
Between 1.615 inches and 1.625 inches
Extended Washer Thickness:
Between 0.212 inches and 0.232 inches
Grip Diameter:
Between 0.998 inches and 0.999 inches
Thread Diameter:
1.000 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, ty2, cl3 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:

N/a

NSN 5306-01-269-9235

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0