

View Online at <https://aerobasegroup.com/nsn/5306-01-269-9235>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.479 inches and 1.519 inches

**Fastener Length:**

Between 3.114 inches and 3.134 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.913 inches and 0.933 inches

**Width Between Flats:**

Between 1.047 inches and 1.062 inches

**Extended Washer Diameter:**

Between 1.615 inches and 1.625 inches

**Extended Washer Thickness:**

Between 0.212 inches and 0.232 inches

**Grip Diameter:**

Between 0.998 inches and 0.999 inches

**Thread Diameter:**

1.000 inches

**Grip Length:**

Between 1.615 inches and 1.635 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2, cl3 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0